amaverick X° xc

IIGHLIGHTS

Front Shocks

Rear Shocks

Rear Suspension

K E S

- 101-hp Rotax[®] 1000R V-twin engine with high-flow dynamics
- 60 in. (152.4 cm) overall width
- Tri-Mode Dynamic Power Steering (DPS[™])
- Visco-Lok[‡] QE auto-locking front differential
- Intelligent Throttle Control (iTC[™])
- Continuously Variable Transmission (CVT) with • Zylon[†]-reinforced belt
- Mid-engine layout for mass centralization ٠
- Double A-arm front suspension with • 12 in. (30.5 cm) of travel
- Torsional Trailing A-arms independent rear suspension (TTA) with 12 in. (30.5 cm) of travel

- Front and rear FOX[†] 2.0 PODIUM[†] C shocks
- 12-in. aluminum beadlock wheels with • 27-in. Maxxis Bighorn 2.0⁺ tires
- High-strength, 200-lb (91 kg) multipurpose • rear rack with LinQ[™] quick-attach system ٠
- Analog / Digital gauge
- Adjustable driver's seat and tilt steering •
- Passenger handhold and grab bar •
- X-package seat trims and graphics



Maxxis Bighorn 2.0 27 x 9 x 12 in. (68.6 x 22.9 x 30.5 cm)

Maxxis Bighorn 2.0 27 x 11 x 12 in. (68.6 x 27.9 x 30.5 cm)

12 in. aluminum beadlock

10 gal (37.8 L)

White, Black & Can-Am Red / 1000R Light Grey & Octane Blue / 1000R

Front Tires

Rear Tires

Wheels

| ENGINE | 1000R | |
|----------------------|---|--|
| Туре | 101 hp, Rotax 976 cc, V-twin, liquid cooled | |
| Fuel Delivery System | Intelligent Throttle Control (iTC) with Electronic Fuel Injection (EFI) | |
| Transmission | CVT with Zylon-reinforced belt, L / H / N / R / P, standard engine brake | |
| Drive Train | Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential | |
| Power Steering | Tri-Mode Dynamic Power Steering (DPS) | |
| SUSPENSIONS | | |
| Front Suspension | Double A-arm | |

wit

Torsional Tra

| Tri-Mode Dynamic Power Steering (DPS) | | | |
|--|-------------------------|--|--|
| | DIMENSIONS / CAPACITIES | | |
| | LxWxH | 118.8 x 60 x 72.2 in. (301.7 x 152.4 x 183.4 cm) | |
| Double A-arm 12 in. (30.5 cm) travel | Wheelbase | 84.3 in. (214.1 cm) | |
| FOX 2.0 PODIUM C Piggyback | Ground Clearance | 11 in. (28 cm) | |
| th compression and preload adjustments | Dry Weight* | 1,297 lb (588 kg) | |
| railing A-arms independent rear suspension (TTA) with sway bar | Rack Capacity | 200 lb (91 kg) with LinQ quick-attach | |
| 12 in. (30.5 cm) travel | Storage Capacity | Glove box: 4.5 gal (17.2 L) | |
| FOX 2.0 PODIUM C Piggyback th compression and preload adjustments | | Under driver seat: 3.5 gal (13.1 L) Center console: 0.3 gal (1.3 L) | |
| | Towing Capacity | N/A | |
| | | | |

| ng A-arms independent rear suspension (TTA) with sway bar | Rack Capacity | |
|---|---------------|--|
| 12 in. (30.5 cm) travel | Storage Capac | |
| FOX 2.0 PODIUM C Piggyback ompression and preload adjustments | | |
| | Towing Capaci | |
| | Fuel Capacity | |
| and dress have to a contract to descend a state of a final sector of the sec- | | |

| 12 m. (30.5 cm) travei |
|--|
| FOX 2.0 PODIUM C Piggyback |
| with compression and preload adjustments |
| |
| |
| |

| Front | Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers |
|-------|--|
| Rear | Dual 214 mm ventilated disc brakes with hydraulic single-piston calipers |

| FEATURES | | | | |
|----------|---|-------------------|--|--|
| Gauge | Multifunction Analog / Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport mode, ECO [™] mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off | Protection | N/A | |
| | | Instrumentation | Lighter type DC outlet in console, standard connector in the back (15-A) | |
| | | Lighting | 240-W from four 60-W projectors with tail lights / brake lights | |
| Winch | Prewired for winch | Anti-theft System | Digitally Encoded Security System (D.E.S.S.™) | |
| WARRANTY | | | | |
| Factory | 6 months limited warranty | | | |
| Extended | B.E.S.T. available from 6 to 30 months | | | |

©2015 Bombardier Recreational Products Inc (BRP). All rights reserved. TM, [®] and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. "Base model dry weight shown. "Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed.



Can-AmOffroad.com