≌OUTLANDER™ MAX XT™

HIGHLIGHTS

- Rotax® V-twin engine options
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- 3,000-lb (1,361 kg) WARN[†] winch with roller fairlead
- Heavy-duty front and rear bumpers
- 12-in. cast-aluminum wheels
- 26-in. Carlisle† ACT radial tires
- · Handlebar wind deflectors
- Convertible Rack System (CRS) with LinQ™ system
- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips

- · Raised floorboards
- 5.7-gal (21.4 L) water-resistant rear compartment
- 625-W magneto



Yellow / 570 / 650 / 850 / 1000R

Brushed Aluminum / 650 / 850 / 1000R

Pearl White / 570 / 650 / 850 / 1000R

Mossy Oak† Break-Up Country Camo† / 650 / 850 / 1000R

ENGINES	570	650	850	1000R
Туре	48 hp, Rotax 570 cc V-twin, liquid cooled	62 hp, Rotax 649.6 cc V-twin, liquid cooled	78 hp, Rotax 854 cc V-twin, liquid cooled	89 hp, Rotax 976 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)			
Transmission	CVT, P / R / N / H / L, standard engine braking			
Drive Train	Selectable 2WD	/ 4WD with Visco-Lo	ok‡ QE auto-locking	front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)			

SUSPENSIONS	
Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent rear suspension (TTI) 9.3 in. (23.6 cm) travel
Rear Shocks	0il

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston calipers

TIRES / WHEELS		
Front Tires	Carlisle ACT radial 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)	
Rear Tires	Carlisle ACT radial 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)	
Wheels	12 in. cast aluminum	

DIMENSIONS /	CAPACITIES
LxWxH	94 x 46 x 53 in. (238.8 x 116.8 x 135 cm)
Wheelbase	59 in. (149.9 cm)
Ground Clearance	11 in. (27.9 cm)
Seat Height	34.5 in. (87.7 cm)
Engine / Dry Weight*	570 / 793 lb (359 kg) 650 / 795 lb (361 kg) 850 / 797 lb (361 kg) 1000R / 824 lb (374 kg)
Rack Capacity	Front: 100 lb (45 kg) Rear: 200 lb (90 kg)
Storage Capacity	Rear: 5.7 gal (21.4 L)
Towing Capacity	1,300 lb (590 kg)
Fuel Capacity	5.4 gal (20.5 L)

FEATURES	
Gauge	Multifunction Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead
Protection	Heavy-duty front & rear bumpers, handlebar wind deflectors

Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Lighting	230-W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
Seat	Convertible Rack System (CRS)
Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)

WARRANTY

Factory 6 months limited warranty

Extended B.E.S.T. available from 6 to 30 months



